




AC microLine® 1250

DOUBLE-SIDE BATCH PROCESSING MACHINE













POWERFUL AND PRECISE

- Designed for high-precision processing of work pieces
- Suited for fine grinding and honing
- Optimum surface quality, flatness, thickness tolerance and plane parallelism with tightest tolerances on the work piece
- AC 1250 can be linked with semi-automatic or fully automatic loading systems

A NEW BENCHMARK DEFINED





HIGHLIGHTS AC microLine® 1250

- Fast and ergonomic loading and unloading
- Upper working wheel can swivel out for optimal access to the process area
- Extreme temperature stabilization over the tool surface
- User friendly, intuitive operation
- Excellent machining results and precision
- Low operating costs
- Individual process development
- Easy to maintain
- High-precise non-contact measuring control
- Powerful drive technology
- High-precise pneumatic load system
- High production reliability
- Stable cast iron base frame
- Siemens PLC Control and Siemens KP1200 Comfort Panel
- Remote maintenance solution RangeCare® via mobile communications or VPN



View from the process area into the Twin Loader – for shortest carrier exchange time



Robot Cell for automatic loading and unloading



Contactless measuring control for highest switch-off accuracy

TECHNICAL DATA	AC microLine® 1250	
VERSION	F	Н
Wheel diameter [mm]	1250	1250
Ring width [mm]	349	349
Max. load pressure [daN]	2500/4000	2500/4000
Upper/lower drive power [kW]	36/70	36
Upper/lower drive speed [rpm]	120/200	120
Center drive power [kW]	6/9	6
Center drive speed [rpm]	65/90	65
Working wheel cooling	wheel cooling	wheel cooling
Machine dimensions [H×W×D] [mm]	2600×2500×2750	2600×2500×2750
Machine weight without switch cabinet [kg]	7800	7800
Max. work piece thickness [mm]	100	100
Max. work piece diameter [mm]	320	320

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

LAPMASTER WOLTERS GMBH

Phone: +49 4331 458 0 ac@lapmaster-wolters.de www.lapmaster-wolters.de