

# Impulse Sealers

## GENERAL INFORMATION

Impulse sealers are instantly ready to use. They are suitable for ready-made bags or tubular film and capable of sealing PE, PP and thin laminates.

### Super Poly

Due to its portable character, this machine is particularly suitable for sealing all kinds of strange and difficult shaped products. The bi-active seal bars (both upper and lower seal bar are equipped with a resistance wire) allows the sealing of thick polyethylene up to 2 x 0,3 mm. Furthermore it will be possible to seal most of the laminate films, a simple test will tell you if the machine will be adequate for your film or not.

| Technical information | 281 PS        | 381 PS        | 631 PS        |
|-----------------------|---------------|---------------|---------------|
| Seal length           | 280 mm        | 380 mm        | 630 mm        |
| Seal width            | 3 mm          | 3 mm          | 3 mm          |
| Max. opening jaw      | 30 mm         | 30 mm         | 30 mm         |
| Weight                | 2,5 kg        | 2,8 kg        | 3 kg          |
| Dimensions (lxwxh)    | 400x350x150mm | 400x450x150mm | 400x700x150mm |



| Technical information | Transformer      |
|-----------------------|------------------|
| Voltage               | 230V-1Ph-50/60HZ |
| Consumption           | 1500W            |
| Weight                | 7 kg             |
| Dimensions (lxwxh)    | 270x190x190mm    |



Super Poly series + Transformer

The machine needs to be connected to a transformer, where the seal time can be set accordingly to the film you are using. Once the jaws are closed the button is pressed and the seal will start, indicated by a control light. After the sealing time has passed (max. 1-3 sec.) the sealing will stop automatically and you can open the tongs.