

# ACCOMMODATION CONTAINER

## Technical Specifications

- ▣ **Structure:** high galvanized and painted steel sandwich panel surface and frame.
- ▣ **Wall:** polyurethane, rockwool or expanded polystyrene foam insulated sandwich panels exterior and interior walls. Wall thickness: **50mm, 60mm, 80mm or 100mm.**
- ▣ **Ceiling:** 40mm or 80mm polyurethane insulated ceiling.
- ▣ **Flooring:** 18mm fibercement panel surface + 03mm PVC flooring. Optional: parquet or ceramic tile. Optional: 50mm or 100mm rockwool floor chassis insulation.
- ▣ **Door and Window Joinery:** Aluminum or PVC windows and doors, window and door protection steel bar (optional).
- ▣ **Lighting (IP65) and Electrical**
- ▣ **Equipment are included**
- ▣ **Sanitary equipment:** Ceramic hand wash 37x45cm, Acrylic shower tray 102x92cm, ceramic wc. Option: **stainless wc and hand wash, cubicle compact laminate wc and shower cabins**
- ▣ **Internal Arrangement (optional):** air conditioning, furniture (steel locker and bench).
- ▣ **Connection Set (optional):** a connection set is provided to be joined together or to facilitate overlapping.
- ▣ **Additional Roofing (optional):** galvanized trapezoidal roof or polyurethane insulated sandwich panel additional roof covering.



20 FEET

**Fully Equipped**  
**Modular Accommodation Container**



40 FEET

