

## PM 401 G RD3 X M9 3 m

094-700002-00600



- Gas-cooled MIG/MAG function torch with high-quality OLED graphic display
- **Display and setting of:**
- Welding current and wire feed speed
- Voltage correction
- Program and JOB selection
- Welding process switching
- Interferences and error messages
- **Xnet support:**
- Selection of welding tasks according to welding sequence plan
- Component management
- Automatic LED lighting when welding torch is moved
- For the Titan XQ puls welding machine – the range of functions may be limited for other welding machines
- Secure hold thanks to rubber inserts in the grip
- The flexible ball joint makes it comfortable to work with, even in difficult spots
- The torch trigger protection prevents the arc being ignited unintentionally
- Safe and rugged; without control cable and additional connector plug
- **Equipment as supplied (steel wire Ø 1.2 mm):**
- Gas nozzle Ø 17 mm; 66 mm
- Gas diffuser Ø 20 mm; 21.5 mm
- Contact tip M9 x 35 mm; Ø 1.2 mm and contact tip holder M9 x 35 mm
- Steel liner red; Ø 2 mm x 4.6 mm

Duty cycle CO2	450 A / 35 %
Duty cycle M21	400 A / 35 %
Duty cycle M21 pulse	260 A / 35 %
Wire Ø	0.8 mm - 2 mm
Connection	Euro torch connector
Hose package length	3 m
Bend angle torch neck	45 °
Operating weight	1.3 kg