


BZ 133A

Setting tool for blind rivets
Pneumatic-hydraulic | with permanent and intermittent extraction



The specialist for blind rivets up to 8.0 mm in diameter!

Special high-strength FERRO® BULB blind rivets (and similar types) are set easily and reliably by the combination of short stroke and **very high setting force (24,000 N!)**.

Our field service would be glad to present all our pneumatic-hydraulic tools to you.
Make an appointment!



Eminently suitable for FERRO® BULB blind rivets!



Nosepieces

321120000124	Nosepiece 4.0 mm
321120000125	Nosepiece 4.8/5.0 mm
321120000126	Nosepiece 6.0 mm
321120000127	Nosepiece 6.4 / 8.0 mm

Spare and wear parts

361122000022	Clamping sleeve
321120000010	Guide sleeve
361122000020	Clamping jaws
321120000014	O-ring clamping mechanism
311045000013	Pressure spring clamping mechanism

Family facts on the **HONSEL** pneumatic tools on page 65.

	2.4	3.0	3.2	4.0	4.8	5.0	6.0	6.4	8.0
					Aluminium				
					Steel				
					Stainless steel				
					Copper alloys				
	4.8 mm								
					24,000 N at 7 bar				
	2.34 kg								
					< 75 dB(A)				
	5-7 bar								
	18 mm								
	3.5 litres								

G 1/4 inside thread, can be fitted on left or right
 • 1x BZ 133A pneumatic-hydraulic riveter in **HONSEL L-Boxx®**
 • 4x nosepiece
 • 1 set of clamping jaws
 • 1 bottle of hydraulic oil with refill unit
 • 2x mandrel collector

Item no. 320.133.000.000





NEW! All pneumatic tools from 2021 in the **HONSEL L-Boxx®**



High-quality, durable plastic housing.



Multiple compressed air connections to ensure the right working position for right-handed and left-handed users at all times.



Integrated hanger bracket for working with balancer.



Individual setting possibilities for the extractor.



Nosepieces stored directly in the base of the tool.

Very flat standard nosepieces for optimum setting.



Cover cap for reliable blind rivet setting without collecting bin.



Large, sturdy collecting bottle for sheared blind rivet mandrels.