



REV	MODIFICATION	DATE	DRAW
D	EN-03-1011	92.10.17	Seven
E	EN-07-0724	96.07.24	SAN
F	EN-10-0202	99.02.03	Stacy

NOTES:
 1. MATERIAL: NYLON-66, UL94V-2, (COMPLY TO RoHS)
 COLOR=NATURAL.
 2. PART NO.
 P-7005-N2W102B1

- SPECIFICATIONS:
- CURRENT RATING: 15A AC,DC MAX
 - VOLTAGE RATING: 300V AC,DC(SINGLE CIRCUIT: 600V)
 - TEMPERATURE RANGE: -25°C TO +90°C
(INCLUDING TEMPERATURE RISE)
 - CONTACT RESISTANCE: INITIAL VALUE/10mΩ MAX.
AFTER ENVIRONMENTAL TESTING/15mΩ MAX.
 - INSULATION RESISTANCE: 1000MΩ MIN.
 - WITHSTANDING VOLTAGE: 1500V AC/MINUTE
 - APPLICABLE WIRE: AWG #24 TO #14, 0.2 TO 2.0mm
 - APPLICABLE PANEL THICKNESS: .031" TO .079"
(0.8 TO 2.0mm)
 - CONTACT JST FOR DETAILS.



DIMENSION IN mm [Inch]		PROD. SPEC.	KINGFONT PRECISION INDUSTRIAL CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE HOUSING FOR 7005RH-02E-V2 CUSTOMER DRAWING	
.X±0.20	X.*±	APPROVE <i>Gromm</i>	FILE NO. KFP-999	DWG NO. P-7005-N2W102B1
.XX±0.15	.X*±	CHECK <i>Jony</i>	SIZE A4	PROJ. SHEET 1 / 1
.XXX±0.10	.XX*±	DRAW <i>Stacy</i>	SCALE 2.5	REV F