



## DSP AND PTS2 SERIES



### Overview

- Type: Hydraulic presses
- Press capacity: 300-20,000 kN
- Application: die testing, tryout and production start-up

### Description

The PTS2 series is designed for prototype production, die set-up and modification work (including drawing, bending and punching tasks).

The DSP series is especially suitable for die spotting. The mechanical micro inching system provides an accuracy of 0,05 mm.

### Technical specifications

Model	DSP-30	DSP-50	DSP-100	DSP-200
<b>Press capacity</b> in kN	300	500	1,000	2,000
<b>Slide stroke</b> in mm	1,700	1,700	1,900	1,900
<b>Daylight</b> in mm	2,200	2,200	2,500	2,500
<b>Working height above floor level</b> in mm	340	340	340	340
<b>Bolster and slide dimensions</b> in mm	3,000 x 2,000	3,000 x 2,000	4,000 x 2,500	4,500 x 2,500

Model	PTS2-500	PTS2-600	PTS2-800	PTS2-1000	PTS2-1200	PTS2-1500	PTS2-2000
<b>Press capacity</b> in kN	5,000	6,000	8,000	10,000	12,000	15,000	20,000
<b>Slide stroke</b> in mm	1,500	1,500	1,500	1,700	1,700	1,900	2,000
<b>Daylight</b> in mm	2,000	2,000	2,000	2,200	2,200	2,500	2,500
<b>Working height above floor level</b> in mm	700	700	700	750	750	850	900
<b>Bolster and slide dimensions</b> in mm	3,000 x 2,000	3,000 x 2,000	3,000 x 2,000	4,000 x 2,500	4,000 x 2,500	4,000 x 2,500	4,500 x 2,500