

LUMIMAX® LED lighting

High-performance lighting products

with integrated controller technology

for continuous, switch or flashing ope-

ration guarantee the utmost functio-

nality and enable the stable, extraneous

light-independent illumination of your

test objects - even for extremely fast

The integration of high-performance LEDs from renowned manufacturers

combined with a very wide range of

optical systems results in irradiances in

new performance classes.

Technology

iiM AG - The company

iiM AG measurement + engineering is developer, manufacturer and distributor of high-quality, high-performance products for Machine Vision.

In Suhl (Thuringia), we develop and manufacture high-performance and highly functional LED lights under the LUMIMAX® brand for Machine Vision applications in a very wide range of industrial areas, such as for the automobile, semiconductor, pharma, food, drinks and tobacco industries.

A second division develops and markets special measuring technology and peripherals for the cable and wire industry to record geometric features, particularly on insulating covers and cable sheathing, in accordance with standards.

A team of over 60 engineers, technicians and skilled workers assists our customers as a partner when realising their challenges.

Service & consulting



Selecting the right lighting is not only an essential part of stable, reproducible quality control and process control - it is also the key to resolving Machine Vision tasks.

What's more, it saves time and money during the planning, start-up and maintenance of Machine Vision solutions in an industrial environment.

This is why we guarantee you an extensive range of services in addition to exceptional product quality.

LUMIMAX

UV lighting

Our team, consisting of technicians and engineers with many years of experience in the field of Machine Vision, is available to you at any time for the following services:

Customer-specific developments & adaptation of products

Loaned equipment and laboratory equipment

Training



Consulting and support







functionality, guarantee you excellent service, and work with regional partners. All of the development and manufacturing takes place in the head office in Suhl. This means our customers benefit from short processing and

Made in Germany - we are committed

to the highest level of quality and

To ensure the high standard of all processes, the iiM AG quality management system is annually audited by DEKRA Certification GmbH in accordance with standard ISO

Experience

We have extensive experience in Machine Vision and can apply this knowledge excellently when designing and realising our products and when providing consulting. We see our customers as partners. We thus rely on continuous and close cooperation.

Contact



iM AG measurement + engineering Neuer Friedberg 5

Phone: (+49) 3681 / 455 19-0 Fax: (+49) 3681 / 455 19-11

Web: www.iiM-AG.com



LIGHTS FOR MACHINE VISION





Luminescence

that occurs during the transition from a stimulated state to the basic state.

light when stimulated. It begins to glow when exposed to a certain wavelength. However, this glowing stops immediately after exposure.

scence and phosphorescence.

Fluorescence

Phosphorescence

continues to glow after exposure has

Perfectly resolved

The great challenge in fluorescence applications in industrial image processing is that the emitted light (fluorescence) has less energy than the radiation required for stimulation. Fluorescence can be clearly identified by the human eye, while the UV radiation of the lighting is hardly perceived. A camera is much more sensitive in the ultraviolet spectrum. The UV light outshines the fluorescence of the stimulated material in the camera image. The contrast is too low for reliable assessment.

A UV application can be optimised and reliably implemented by precisely coordinating lighting and lens filters. These allow the exact separation of stimulation and emission wavelengths. Interfering UV reflections and extraneous light influences are suppressed. As a result, fluorescent features appear brightly illuminated in the test




image aquisition without lens filter, without lighting filter




image aquisition with lens filter, without lighting filter




image aquisition with lens filter, with lighting filter

Fluorescence applications

UV lights are used to make invisible features on products visible. The UV radiation causes certain materials to glow. This glowing is clearly visible to the human eye and cameras.

Product labels that consumers find annoying can be applied with transparent, fluorescent ink. However, under UV radiation, the labelling can be made visible for the purposes of inspection.

Fluorescent, low-contrast adhesives, paints and seals can be shown in high contrast with ultraviolet radiation. Presence and completeness monitoring is thus made easier for the camera.

The finest cracks, such as in cast parts, can be made visible with the aid of fluorescence.

The areas of application for UV lighting are very diverse. A few examples:

- Inspection of safety features and markings as protection against plagiarism and counterfeiting
- Inspection of adhesives, paints, lubricants and sealant
- Product labelling
- Track & trace
- Residue and residual dirt analyses
- Inspections of cracks, cavities and defects
- Forensic analyses



Industrial & innovative:

High-quality power LEDs in a functional aluminum housing guarantee optimal temperature management and thus stable light conditions as well as a long

Speedy and secure:

Reduction of extraneous light and motion blurring due to fast, high-performance

■ Precise & perfect:

Lighting systems and well-suited accessories like filters perfectly fitting to your application

■ Plug & Play:

Fast and simple integration using functional accessories and a standardised connection concept

Service & Support:

Feasibility studies by experienced employees and free loaning of components assist you during your realisation phase

Perfectly coordinated filters

High-quality filter combinations

emission wavelengths.
UV reflections from the lighting and extraneous light influences are sup-

The result:

LUMIMAX® UV lighting

Lighting:

- LED spots 5W
- LED area flood light LQ100
- LED ring flood light LR70
- LED bar lights LB125 and LB250

Options:

- Operating types: continuous, switch, flashing operation
- UV365 and UV400: Selection of the optimum stimulation wavelength
- Lighting filters: coordinated to the lighting geometry and wavelength
- Option to change lenses: flexible adaptation of the light distribution characteristics





