

IT10

IT10

IT15

IT20

Macchina interceppo singola per le file più strette.

IT21

Single inter-row cultivator for the narrowest rows.

IT30

Machine intercep simple pour les rangés plus étroites.

IT40

Einseitiger Unterstockräumer für die schmälisten Reihen.

IT110

Scopri di più su questo prodotto:

IT115

Find out more on this product:

En savoir plus sur ce produit:

Mehr dazu um dieses Produkt:

IT200



CT20

CT50



CT60

PA10

PA20

Misure di lavoro

Working dimensions - Mesures de travail - Arbeitsmaße

	Attacco telaio Frame attachment Attache du châssis Rahmenanschluss	Peso Weight Poids Gewicht	 min.	
IT 10 H	3 punti posteriore Rear 3-point 3 points arrière	140 kg	165*	min. 85* max. 110*
IT 10 E	3-Punktanbau hinten	160 Kg	165*	min. 85* max. 110*
IT 10 A	Anteriore con staffa Front on bracket Support de fixation avant Vorne auf Formkasten	210 kg	180*	min. 85* max. 110*
IT 10 3A	Anteriore su sollevatore Front lifter Rélévage avant Vorne auf Heber	195 Kg	180*	min. 100* max. 125*

H - Idrraulico - Hydraulic - Hydraulique - Hydraulisch

E - Elettro-Idraulico - Electro-hydraulic - Électro-hydraulique - Elektrohydraulisch

Flusso olio 12÷15 L/min - Oil flow rate 12÷15 L/min - Débit d'huile 12÷15 L/min - Ölfluss 12÷15 L/min

* Considerando carreggiata trattore agricola di 120 cm - Considering tractor's roadway width of 120 cm
En considérant une largeur de route du tracteur de 120 cm - Angenommene Breite des Schleppers von 120 cm

ATTREZZI • p. 22-26

Tools - Outils - Werkzeuge



T1



T2



T3



T4



T5



T6



T7



T8



P1



P2



P3



P4



E1



E2

