

# Kabelverschraubungen / Cable Glands

wege® S Standard UD



<b>Material</b>	Edelstahl 1.4571
<b>Dichteinsatz</b>	TPE
<b>O-Ring</b>	NBR-Oz
<b>Schutzklasse</b>	IP66/ IP68 - 5 bar
<b>Zugentlastung</b>	DIN EN 62444 Tab. 2A
<b>Temperaturbereich</b>	-40 °C bis +100 °C

<b>material</b>	stainless steel AISI 316 Ti
<b>sealing insert</b>	TPE
<b>o-ring</b>	NBR-Oz
<b>protection class</b>	IP66/ IP68 - 5 bar
<b>strain relief</b>	DIN EN 62444 Tab. 2A
<b>range of temperature</b>	-40 °C to +100 °C

Gewinde thread			H	L		Bestell-Nr. ref.-number
-------------------	--	--	---	---	--	----------------------------

## Zweiteiliger Dichteinsatz / two-piece sealing insert

kurzes Anschlussgewinde / short connection thread							
M 16 x 1,5	5	– 10	17	22	5,5	50	389.1600.0
M 20 x 1,5	8	– 14	22	24	6	50	389.2000.0
M 25 x 1,5	12	– 19	30	28	7	25	389.2500.0
M 32 x 1,5	15	– 22	34	30	8	25	389.3200.0
M 40 x 1,5	22	– 28	44	35	8	10	389.4000.0
M 50 x 1,5	28	– 36	54	43	9	5	389.5000.0
M 63 x 1,5	34	– 49	66	48	10	5	389.6300.0

## Einteiliger Dichteinsatz / one-piece sealing insert

kurzes Anschlussgewinde / short connection thread							
M 12 x 1,5	5	– 7	14	20	5	50	389.1200.1
M 16 x 1,5	8	– 10	17	22	5,5	50	389.1600.1
M 20 x 1,5	11	– 14	22	24	6	50	389.2000.1
M 25 x 1,5	15	– 19	30	28	7	25	389.2500.1
M 32 x 1,5	19	– 22	34	30	8	25	389.3200.1
M 40 x 1,5	25	– 28	44	35	8	10	389.4000.1
M 50 x 1,5	32	– 36	54	43	9	5	389.5000.1
M 63 x 1,5	43	– 49	66	48	10	5	389.6300.1

