

PRODUCT INFORMATION

CADAOIL GEARBOX 80W-90 GL5

Mineral gear oil for hypoid gears and hub reductions

Gearbox 80W-90 GL5 is a mineral gear oil, formulated according to the latest phosphor – sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

Gearbox 80W-90 GL5 contains special additives, leaving a protecting oil film for optimum corrosion protection. Furthermore, the SAE 80W-90 viscosity grade has an excellent low temperature fluidity for an optimum performance during all seasons.

Gearbox 80W–90 GL5 shows an excellent oxidation and thermal stability. Seals are not affected by this product.

Gearbox 80W–90 GL5 is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL–5 , MIL–L 2105–D and Mack GO–G are recommended.

PERFORMANCE

API GL-5 MIL-L-2105 B/C/D

Density at 20°C	0,8833 kg/l
Viscosity, kinematic at 100°C	14,1 cSt
Viscosity, kinematic at 40°C	136,9 cSt
Viscosity Index	100
Flash point	243 °C
Freezing point	-33 °C

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

38 Avenue De Waterloo 6000 Charleroi BELGIQUE | M +32 483 70 99 93 | F +32 71 50 27 34 E info@cadaoil.be | W www.cadaoil.be