



CONTINUOUS FORM FILL AND SEAL MACHINE

# paper X (hybrid) FOR FILM AND PAPER PACKAGING





## paper X paper X hybrid

Film or paper? Stay flexible! The paper X hybrid is designed for packaging goods in paper or film. A simple changeover ensures you are ready for the new product and the new packaging material.

Whether using a chain infeed or infeed conveyor, the machines stand apart through their continuous packaging process – without stop-and-go – maximising efficiencies by ensuring there is no downtime when sealing or glueing.


Different machine versions are available, depending on how flexible you need to be:

- the **basic model paper X features paper packaging** with overlap on top
- the **paper X e-com features paper packaging** with overlap on top for different product lengths
- the **paper X hybrid features paper and film packaging** with overlap on top
- the **paper X hybrid advance features paper and film packaging** with overlap on top and side seal



## HIGHLIGHTS

- One single machine for different packaging materials and types
- Quick changeover in approx. 30 to 60 minutes between paper and film
- Extremely high flexibility, future-proofing your packaging requirements
- Siemens TIA Portal or Rockwell Automation control system; free remote service
- Easy line integration and connectivity with higher-level systems, Industry 4.0 Ready
- Optional monitoring, analysis and visualisation of machine and operating data via the Hugo Beck Cockpit

### PAPER



### FILM



### TECHNICAL DATA

|                       |   |
|-----------------------|---|
| <b>Product infeed</b> | manual as standalone/automatic in line  |
| <b>Product sizes</b>  | <b>film:</b> L: from 45 mm, W: max. 450 mm, H: max. 80 mm<br><b>paper:</b> L: from 100 mm, W: max. 625 mm, H: max. 50 mm/only for paper X e-com max. 100 mm |
| <b>Film</b>           | centre-folded and flat film, e.g. PE, PO, PP, bio films, recycled content films   |
| <b>Paper</b>          | uncoated and coated, from approx. 60 g/m <sup>2</sup> to 120 g/m <sup>2</sup>   |
| <b>Capacity</b>       | <b>film:</b> up to 15.000 cycles/h<br><b>paper:</b> 3.000 – 12.000 cycles/h   |
| <b>Versions</b>       | <b>film:</b> side seal, top overlap sealing<br><b>paper:</b> top overlap glued (alternative closing techniques upon request)                                |

### Hugo Beck Maschinenbau GmbH & Co. KG

Daimlerstrasse 26 – 32, 72581 Dettingen/Erms, Germany  
Tel.: +49 7123 7208-0, Fax: +49 7123 87268  
info@hugobeck.de, www.hugobeck.com

**HUGO BECK**  
We package your world