



Kabelverschraubungen / Cable Glands

wege® M Classic 6-kant / hexagonal

Material	Messing vernickelt
Dichtring	<ul style="list-style-type: none"> ① NR/NBR ② CR/EPDM
Schutzklasse	IP54
Temperaturbereich	<ul style="list-style-type: none"> ① -40 °C bis +90 °C ② -30 °C bis +120 °C

material	brass nickel-plated
sealing ring	<ul style="list-style-type: none"> ① NR/NBR ② CR/EPDM
protection class	IP54
range of temperature	<ul style="list-style-type: none"> ① -40 °C to +90 °C ② -30 °C to +120 °C



Gewinde thread		Dichtring sealing ring	SW1	SW2	H	L		Bestell-Nr. ref.-number
-------------------	--	---------------------------	-----	-----	---	---	--	----------------------------

kurzes Anschlussgewinde / short connection thread

M 12 x 1,5	4	-	6	S	②	12	14	15	5	100	111.1200.0
M 16 x 1,5	2	-	10	UNI	②	16	18	16	5	100	111.1600.7
M 16 x 1,5	8	-	10	S	②	15	18	16	5	100	110.1609.0
M 20 x 1,5	3	-	14	UNI	②	20	22	19	6	50	111.2000.7
M 20 x 1,5	8	-	10	S	①	18	22	17	6	50	110.2011.0
M 20 x 1,5	10	-	12	S	①	20	22	19	6	50	110.2013.0
M 20 x 1,5	12	-	14	S	①	22	24	20	6	50	110.2016.0
M 25 x 1,5	7,5	-	18	UNI	②	25	27	22	7	50	111.2500.7
M 25 x 1,5	17	-	19	S	①	28	30	22	7	50	110.2521.0
M 32 x 1,5	15	-	25	UNI	②	32	34	24	8	25	111.3200.7
M 32 x 1,5	26	-	27	S	①	37	39	25	8	25	110.3229.0
M 40 x 1,5	22	-	33	UNI	②	40	42	26	8	20	111.4000.7
M 40 x 1,5	23	-	34	UNI	①	47	50	30	8	10	110.4036.6
M 50 x 1,5	31	-	42	UNI	②	50	52	29	9	5	111.5000.7
M 50 x 1,5	39	-	41	S	①	54	57	34	9	5	110.5042.0
M 63 x 1,5	40	-	51	UNI	②	64	66	35	10	5	111.6300.7
M 63 x 1,5	35	-	46	UNI	①	60	66	36	10	5	110.6348.6

Pg 7	4	-	6	S	②	13	14	15	5	100	110.0700.0
Pg 9	8	-	10	S	②	15	17	16	6	100	110.0900.0
Pg 11	8	-	10	S	①	18	20	17	6	50	110.1100.0
Pg 13,5	10	-	12	S	①	20	22	19	6,5	50	110.1300.0
Pg 16	12	-	14	S	①	22	24	20	6,5	50	110.1600.0
Pg 21	17	-	19	S	①	28	30	22	7	50	110.2100.0
Pg 29	26	-	28	S	①	37	40	25	8	25	110.2900.0
Pg 36	23	-	34	UNI	①	47	50	29	9	20	110.3600.6
Pg 42	39	-	41	S	①	54	57	33	10	10	110.4200.0
Pg 48	35	-	46	UNI	①	60	64	36	10	5	110.4800.6

G 1/2"	7	-	13	UNI	①	20	22	20	6,5	50	110.1312.6
G 3/4"	8	-	18	UNI	②	25	27	22	7	50	110.0034.7
G 2"	35	-	45	UNI	①	60	64	36	10	5	110.0200.6

Gewinde thread		Dichtring sealing ring	SW1	SW2	H	L		Bestell-Nr. ref.-number
-------------------	---	---------------------------	-----	-----	---	---	---	----------------------------

langes Anschlussgewinde / long connection thread

M 12 x 1,5	4 – 6	S	②	12	14	15	10	100	121.1200.0
M 16 x 1,5	2 – 10	UNI	②	16	18	16	10	100	121.1600.7
M 16 x 1,5	4 – 11	UNI	②	15	18	16	10	100	120.1609.6
M 20 x 1,5	3 – 14	UNI	②	20	22	19	10	50	121.2000.7
M 20 x 1,5	6,5 – 13,5	UNI	①	18	22	17	10	50	120.2011.6
M 20 x 1,5	6,5 – 13,5	UNI	①	20	22	19	10	50	120.2013.6
M 20 x 1,5	6,5 – 16	UNI	①	22	24	20	10	50	120.2016.6
M 25 x 1,5	7,5 – 18	UNI	②	25	27	22	11	25	121.2500.7
M 25 x 1,5	9 – 20	UNI	①	28	30	22	11	50	120.2521.6
M 32 x 1,5	15 – 25	UNI	②	32	34	24	13	25	121.3200.7
M 32 x 1,5	17 – 28	UNI	①	37	39	25	13	25	120.3229.6
M 40 x 1,5	22 – 33	UNI	②	40	42	26	13	20	121.4000.7
M 40 x 1,5	23 – 34	UNI	①	47	50	30	13	10	120.4036.6
M 50 x 1,5	31 – 42	UNI	②	50	52	29	14	5	121.5000.7
M 50 x 1,5	29 – 40	UNI	①	54	57	34	14	5	120.5042.6
M 63 x 1,5	40 – 51	UNI	②	64	66	35	14	5	121.6300.7
M 63 x 1,5	35 – 46	UNI	①	60	66	36	14	5	120.6348.6

Pg 9	4 – 11	UNI	②	15	17	16	15	100	120.0900.6
Pg 11	6,5 – 13,5	UNI	①	18	20	17	15	50	120.1100.6
Pg 13,5	6,5 – 13,5	UNI	①	20	22	19	15	50	120.1300.6
Pg 16	6,5 – 16	UNI	①	22	24	20	15	50	120.1600.6
Pg 21	9 – 20	UNI	①	28	30	22	15	50	120.2100.6
Pg 29	17 – 28	UNI	①	37	40	25	15	25	120.2900.6
Pg 36	23 – 34	UNI	①	47	50	29	15	20	120.3600.6
Pg 42	29 – 40	UNI	①	54	57	33	15	10	120.4200.6

G 2 1/4"	46 – 48	S	①	44	70	39	14	5	120.0214.0
G 2 1/2"	46 – 60	UNI	②	80	80	37	20	3	120.0212.7
G 3"	67 – 69	S	①	95	95	52	20	3	120.0300.0
G 3"	60 – 70	UNI	②	95	95	52	20	3	120.0300.7

Universal (UNI) Dichtring
Universal (UNI) sealing ring



Standard (S) Dichtring
Standard (S) sealing ring

