

Perforated Metal Plank Type BN-033

The perforated metal planks, type BN-033 'Noppe, offen' combines top and bottom pressed nubs with a hole diameter of 8 mm: This provides excellent stability and drain holes for a good drainage effect. In combination with the profile BN-033vi for steps with vi-nosing or the closed profile BN-G33 it results in many applications and variations

Technical Details

Material	Steel S235JR:	2,0 mm, 2,5 mm
	Stainless Steel:	1,5 mm 2,0 mm,
	Aluminium:	2,0 mm, 2,5 mm
Surface treatment	Steel:	untreated, hot-dip galvanized, pre-galvanized
	Stainless Steel:	untreated, pickled
	Aluminium:	untreated, pickled, anodized
Free cross section	Max. ~ 5 %	
Width	150 mm, 200 mm, 250 mm, 300 mm (other widths possible in demand)	
Height	30 mm, 50 mm, 75 mm, 100mm, 150 mm Corresponding to width and statical specification)	
Ball proof	Ø 10 mm (the Ø 10 mm ball don't fall through)	
Slip resistance	R11 / V10 (Steel hot-dip galvanized IFA1504066)	
Longitudinal grid	133,33 mm (66,66 mm)	
Production length	max. 10 m, depending transport limited	

