



ACCESSORIES

PRESSURE REGULATORS, GAS HOSE, GROUND CABLES



Item number



Purging

TIG (orbital)

The cylinder pressure regulator with manual connection reduces the cylinder pressure of compressed gases and gases dissolved under pressure of max. 200 bar (300 bar on request) to a pressure corresponding to the flowmeter. The desired flow rate in l/min can be constantly set on the flowmeter.

Important: This pressure regulator has a constant working pressure of 2.5 bar to protect the orbital system's gas flow sensor.

Control range:

Twin flow 1 – 15 l/min, 3 – 25 l/min

Triple flow 1 – 15 l/min, 3 – 25 l/min, 5 – 50 l/min



Purging

TIG (manual)

TIG (orbital)

SPECIAL ARGON PRESSURE REGULATOR with twin flowmeter, brass

1.2.0123

SPECIAL PRESSURE REGULATOR with twin flowmeter for H2 gases, brass

1.2.0144

SPECIAL ARGON PRESSURE REGULATOR with triple flowmeter, brass

1.2.0134



200 / 10 BAR ARGON PRESSURE REGULATOR

(for RBK 60 S pneumatic connection)

1.2.0150



0.5 – 10 BAR COMPRESSED AIR PRESSURE REGULATOR

incl. mounting bracket and inlet and outlet coupling
(for RBK 60 S pneumatic connection)

1.2.0151

Pressure regulators with different connections and for other gas types or nickel-plated version available on request.



GAS HOSE, 3 m

1.3.0121



GROUND CABLE, 5 m, 35 mm², up to 300 A

1.3.0125



GROUND CABLE, 5 m, 50 mm², up to 500 A

1.3.0146

Orbital welding systems

Welding tools

Welding accessories

Joint preparation

Purging accessories

Measuring devices

Service / general