



Pin Type	Interface Dim L	Pin Type	REV	MODIFICATION	DATE	DRAW
Detect	3.5 mm	25,26				
General	4.25 mm	All Other Pins				
Power	5.0 mm	1,13,38,50				

SPECIFICATIONS:
 HOUSING : High Temperature Plastic, UL 94V-0
 CONTACT : Copper Alloys
 VOLTAGE RATING : 100VAC
 CURRENT RATING : 0.5A
 CONTACT RESISTANCE:40 m Ohm max.
 INSULATION RESISTANCE:1000M Ohm min.
 DIELECTRIC STRENGTH : 500VAC/1min
 OPERATION TEMPERATURE : -40°C~85°C
 Ordering Information:CFCMD-45T xx W106

Contact Area Plating: _____
 15--15U" Gold Plating.
 Color: _____
 W-White

DIM-A 6-38.74+CAP,T/R

DIMENSION IN mm [Inch]		PROD. SPEC	KINGFONT PRECISION INDUSTRIAL CO., LTD.	
		SP0028	KINGFONT PRECISION INDUSTRIAL CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC	TITLE	CUSTOMER DRAWING
		PP-CFC-016	CF CARD TYPE2 STANDOFF 2mm NORMAL TYPE + CAP	
.X±0.30	X.'± 1'	APPROVE	FILE NO. KFP-028	DWG NO. CFCMD-45TxxW106
.XX±0.20	.X.'± 0.5'	CHECK	SIZE	PROJ. SHEET 1 / 1
.XXX±0.10	.XX.'± 0.25'	DRAW	SCALE 1:1	REV A