# PURGE PRESSURE ANALYSER

ACCESSORIES, PPA 2500



Item number

1.3.5009

Orbital welding Orbital welding



### COM-CABLE OXY 2 / EVO FOR COMMUNICATION AND **DOCUMENTATION**

**COM-CABLE** for connection Oxy 2 / EVO to controllers TIGTRONIC BASIC 2-4

COM-CABLE OXY 2 / EVO for connection to controllers TIGTRONIC ORBITAL 4, COMPACT and EVO

1.3.5011

1.3.5014

1.3.5015

1.3.5200



#### **SPARE FILTER**

## **PURGE PRESSURE ANALYSER PPA 2500**

**SPARE PLASTIC HOSE** for OXY 2, 3 and EVO 3m, with particle filter and stainless steel probe

The PPA 2500 purge pressure analyser is used for setting an monitoring the ID purge pressure. It replaces the analogue Magnahelic devices traditionally used for applying the ID pressure balancing technique used for producing high-quality " controlled profile" welds on small diameter applications. The connection with the TIGTRONIC ORBITAL 4, TIGTRONIC COMPACT and EVO controllers enables documentation.



24V (via the controller)

0 - 2500Pa Weight 0.6kg

Dimensions (L x W x H) 41mm x 80mm x 160mm

## Package includes:

- Purge Pressure Analyser
- Sampling Hose 6mm T-fitting
- Calibration certificate
- Plastic box



53