



REV	MODIFICATION	DATE	DRAW
B	EN-02-1014	91.10.21	ERICA
C	EN-07-0812	96.08.07	SAN

SPECIFICATIONS:

- CURRENT RATING: 15A AC,DC MAX
- VOLTAGE RATING: 300V AC,DC(SINGLE CIRCUIT: 600V)
- TEMPERATURE RANGE: -25°C TO +90°C
(INCLUDING TEMPERATURE RISE)
- CONTACT RESISTANCE: INITIAL VALUE/10mΩ MAX.
AFTER ENVIRONMENTAL TESTING/15mΩ MAX.
- INSULATION RESISTANCE: 1000MΩ MIN.
- WITHSTANDING VOLTAGE: 1500V AC/MINUTE
- APPLICABLE WIRE: AWG #24 TO #14,0.2 TO 2.0mm
- APPLICABLE PANEL THICKNESS: .031" TO .079"
(0.8 TO 2.0mm)
- CONTACT JST FOR DETAILS.

NOTES:

1.MATERIAL : NYLON 66 (COMPLY TO RoHS)

2.PART NO. :

P-7006-XX X 10300

MATERIAL COLOR
 N1:NYLON 66 94V-0, M:MILK WHITE
 N2:NYLON 66 94V-2 W:WHITE



DIMENSION IN mm [inch]		PROD. SPEC.	C KINGFONT KINGFONT PRECISION INDUSTRIAL CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE PH7006P03B HSG. CUSTOMER DRAWING	
.X±0.20	X.±	APPROVE <i>Sam</i>	FILE NO.	DWG NO. P-7006-XXX10300
.XX±0.10	.X.±	CHECK <i>Tony</i>	SIZE A4	PROJ. SHEET 1 / 1
.XXX±	.XX.±	DRAW <i>Sam</i>	SCALE 3:1	REV C