

GROUNDING CONTROL DEVICE EKX-4 LT

THE EAC EX APPROVED LOW TEMPERATURE VERSION

The Grounding Control Device EKX-4 LT is the specialized **cold-proof version** of the standard EKX-4 device suitable for use in extremely **low ambient temperature** (e.g. in Siberia). An additional housing with a **self-regulating** heating combined with our special cold-resistant grounding cable allows utilization in a temperature range from **+ 50 °C down to - 55 °C**.

FUNCTIONAL PRINCIPLE

EKX-4 LT ensures that **static electricity is discharged to the ground by a grounding cable** and **continuously monitors grounding quality**. Only if the connected tank vehicle is detected and grounded properly, the filling release will be signaled by clearly visible green LEDs and control outputs. If there are any breaks in the grounding connection, the LEDs will change to red and filling will be interrupted immediately.

APPLICATION AREAS

EKX-4 is mounted stationary **at the loading site**. It is suitable for operation in gas and dust hazardous areas of **zone 1 and 21** – mainly in the petrochemical and chemical industry. EKX-4 LT has been developed in accordance with the technical regulation **TR CU 012/2011** of the **Eurasian Customs Union** (EAC Ex approval).

PRODUCT BENEFITS

- **Prevents manipulation** due to object recognition (by measuring the impedance)
- Automatic diagnosis system **self-monitors** all safety-related functions **continuously**
- Possibility to **connect longer cables** (up to 30 m) due to cable compensation
- **Simple device configuration** (e.g. "road tank truck", "railway tank wagon")
- **Opening the housing** under voltage is permissible – thanks to intelligent explosion protection (IEPC)



HIGHEST LEVEL OF SAFETY
in hazardous areas

LEADING TECHNOLOGY
in monitoring, diagnostics, and configuration

EASY TO OPERATE
by ability to open housing in hazardous areas



EKX-4 LT



TECHNICAL SPECIFICATIONS

Type of protection:

according to TR-CU 012/2011:

1Ex e q [ib] IIC T4 Gb X

Ex tb [ib Db] IIIC T80°C Db X

Power supply:

230 V AC \pm 10 %, 50-60 Hz, about 75 VA

Control outputs:

2 potential-free closing contacts

1 change-over contact | 1 NAMUR-output

Operating temperature: - 55 °C up to + 50 °C

Approval: TR-CU 012/2011

ACCESSORIES*

CLAMP AND CABLE




Grounding clamp




Low temperature grounding cable
up to 30 m

CLAMPS

Breakaway coupling - option 1



Breakaway coupling - option 2



OTHER ACCESSORIES



Testing equipment



Clamp hanger

*For further information and additional accessories, visit us at www.timm-technology.de or contact us in person.



H. TIMM ELEKTRONIK GmbH

Senefelder-Ring 45
21465 Reinbek
Germany

Tel. +49 40 248 35 63 - 0
info@timm-technology.de
www.timm-technology.de