

# IT115

**Macchina interceppo singola indipendente larga, equipaggiata con serbatoio idraulico, radiatore e due pompe (25 + 16 L/min).**

Single large independent inter-row cultivator, equipped with oil tank, oil cooler and two pumps (25 + 16 L/min).

Machine intercep simple indépendante large, équipée avec centrale hydraulique, radiateur de refroidissement et deux pompes (25 + 16 L/min).



Einseitiger unabhängiger breiter Unterstockräumer, mit hydraulischem Ölbehälter, Ölkühler und zwei Pumpen (25 + 16 L/min) ausgestattet.

Scopri di più su questo prodotto:  
Find out more on this product:  
En savoir plus sur ce produit:  
Mehr dazu um dieses Produkt:



## Misure di lavoro

Working dimensions - Mesures de travail - Arbeitsmaße

	Attacco telaio Frame attachment Attache du châssis Rahmenanschluss	Peso Weight Poids Gewicht		
<b>IT 115 H</b>	3 punti posteriore Rear 3 points 3 points arrière 3-Punktanbau hinten	270 kg	180*	min. 110* max. 150*
<b>IT 115 E</b>		290 Kg	180*	min. 110* max. 150*
<b>IT 115 A</b>	Anteriore su sollevatore Front lifter Rélévage avant	295 kg	180*	min. 110* max. 170*
<b>IT 115 3A</b>	Vorne auf Heber	295 kg	180*	min. 110* max. 170*

H - Idraulico - Hydraulic - Hydraulique - Hydraulisch

E - Elettro-Idraulico - Electro-hydraulic - Électro-hydraulique - Elektrohydraulisch

\* Considerando carreggiata trattore agricola di 160 cm - Considering tractor's roadway width of 160 cm  
En considérant une largeur de route du tracteur de 160 cm - Angenommene Breite des Schleppers von 160 cm

IT10

IT15

IT20

IT21

IT30

IT40

IT110

**IT115**

IT200

CT20

CT50

CT60

PA10

PA20

## ATTREZZI • p. 22-26

Tools - Outils - Werkzeuge

