



PRODUCT INFORMATION

CADAOIL GEARBOX ATF VI

Fully synthetic automatic transmission fluid

Cadaoil Gearbox ATF VI is a fully synthetic transmission fluid, especially developed for automatic transmissions of General Motors. It is also suitable for power steering systems and some hydraulic systems where a good low temperature fluidity is required.

Cadaoil Gearbox ATF VI has an extremely low pour point, allowing easy gear shifting at cold starts. Seals are not affected by this fluid.

Cadaoil Gearbox ATF VI is the recommended top-up or refill fluid for automatic transmissions where DEXRON VI and/or DEXRON III is prescribed.

Versus DEXRON III, Cadaoil Gearbox ATF VI has a very high and stable viscosity index and an improved resistance against corrosion and oxidation. Due to these improvements, the drain interval for new GM automatic transmissions is doubled.

Cadaoil Gearbox ATF VI meets the DEXRON VI specification which is especially developed for the new Hydra-Matic sixspeed transmission of General Motors. This ATF is required in all automatic transmissions of General Motors build in 2006 or later.

PERFORMANCE

GM Dexron VI

GM Dexron III

MB 236.41

BMW 83 22 0 397 114

Colour	Red	
Density at 20°C	0.8426 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	31.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.2 cSt	ASTM D 445
Viscosity Index	152	ASTM D 2270
Flash point	211 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.